



Typical Inspection Data:

Density @ 20°C	1.125 g/cm ³
Appearance	Clear, Green
Boiling point	170°C
Reserve Alkalinity	9.5 ml
Water Content	3.5%
Refractive Index	1.432

Protection Levels:

Xstream® G64® (%)	Approx. Protection (°C)
33	-18
50	-37

Xstream® G64® Antifreeze & Coolant Concentrate

Glysantin® G64® by BASF is approved by:

Volvo Cars TR-31854114-002,
Deutz DQC CC-14, Deutz-Fahr, Huerlimann, Lamborghini
Tractors, MAN Turbo & Diesel, Same
Conforms to the requirements of BS 6580:2010

Product Features:

- Ethylene glycol based antifreeze and coolant with silicate based inhibitors
- Protects against corrosion, overheating and freezing
- Typical service life of up to 5 years
- Safeguarded with bittering agent to help prevent accidental ingestion
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com

Direction of use:

- Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions
- Pour into vehicle cooling system
- Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook
- Remove spills from paintwork immediately

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried
- Wash off any spillage on paintwork immediately
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product

Shelf Life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 27/03/19